



Autumn Liu
Overseas Sales Director
Mobile: 0086 13632608069
E-mail: autumn@weony.com

Weony Industrial Limited

Factory details Tel:0086-755-23348674 Fax:0086-755-2312 8991
Address: 4th building, Hi-tech Industrial Zone, Heping Community,
Fuyong, Baoan District, Shenzhen, 518103, P.R. China
Website: www. weony. com

HK financial office details Tel: 00852-2297 9277 Fax: 00852-2297 9269
Address: 16/F, Kowloon Building, 555 Nathan Road, Mongkok, Kowloon, HK



CONTACT US

Factory details

Tel: 0086-755-23348674 Fax: 0086-755-23128991
Add: 4th building, Hi-tech Industrial Zone, Heping Community,
Fuyong street, Bao'an District, Shenzhen, Guangdong, China 518103
Website: www.weony.com

HK financial office details

Tel: 00852-2297 9277
Fax: 00852-2297 9269
Add: 16/F, Kowloon Building, 555 Nathan Road, Mongkok, Kowloon, HK



PRODUCT CATALOGUE 2018



SFDA FSC RoHS REACH PAHs Phthalates

WEONY

Weony Your Reliable Partner



Weony is a professional manufacturer in the healthcare industry developing digital blood pressure monitors, digital thermometers, infrared thermometers, non-contact forehead thermometers, compressor nebulizers and related healthcare products. Quality and Credibility are what we emphasize in the development of our competitive market and customer satisfaction. Quality has a more human aspect than either costs or productivity. Additionally, improving quality in creative can lead to lower costs and higher productivity. These concepts form the basis of our philosophy. Quality is the key to competitiveness and has become a fundamental way of managing business for market growth and profitability. We're fully committed to providing our customers with the highest quality products, and with the most competitive prices. We have a team providing strong support service and after-sales-service to our respectable customers around the globe. These things work as we have been gaining much reputation of being a reliable manufacturer in the healthcare and even in the medical industries.

We are pleased to accept OEM, ODM, Turnkey Project, etc. for customers from around the world. We have a great sales team to follow your projects and a professional production staff to take care of your orders making sure that the products you order are produced at the highest quality. We truly believe that low-cost products are not necessarily to be poor in quality. We make products for less money but for higher return.

We are currently exporting our products to Europe, Asia, North and South America and so on, for a total of over ninety countries.

Keeping people healthy is a long way to go. We are going to develop our own IoT platform to further enhance our service and capability. We are seeking interested parties to join us as strategic partners entering into this new era of opportunity, and opening a new page of the healthcare industry.

QUALITY FIRST, CREDIBILITY FIRST



CE Certificate



ISO13485



FSC



FDA



upper arm SFDA



wrist SFDA



RoHS test report



Phthalates test report



REACH test report



PAHs test report



BSCI

NEW DESIGNS



U820



U801



UFR105

UPPER ARM Blood Pressure Monitors

- Voice Function (option)
- 1 Color Backlit LCD Display (option)
- 3 Colors Changing Indication LCD Display (option)
- Bluetooth Function (option)



U828

LCD size: 81x27mm with digit height 16mm
Product size: 118x70x27.5mm
Buckle Fixed CUFF Arm Type BPM
Acrylic front panel
Power by 4 AAA size alkaline batteries or micro USB power supply

U80S

LCD size: 81x27mm with digit height 16mm
Product size: 137x75x27.5mm

Buckle Fixed CUFF Arm Type BPM
Acrylic front panel
Power by USB rechargeable Li-battery (option) or 4 AAA size alkaline batteries or AC/DC power supply

- 2x90 memory
- 3 times average
- IHB indicator
- Year/month/date/time function
- Accuracy: Pressure ± 3 mmHg; Pulse $\pm 5\%$
- Automatic power-off function



U80R

LCD size: 80x58mm with digit height 25mm
Product size: 139x95x34mm

Acrylic front panel and Ultra-thin cosmetic design



U80RH

LCD size: 80x58mm with digit height 25mm
Product size: 139x95x34mm

Touch button controlling
Acrylic front panel and Ultra-thin cosmetic design



U80QH

Large LCD size: 98.2x69.4mm
Product size: 135.8x122x50mm

Touch button controlling
Blue backlight for LCD



- 2x90 memory
- 3 times average
- WHO indicator
- IHB indicator
- Year/month/date/time function
- Accuracy: Pressure ± 3 mmHg; Pulse $\pm 5\%$
- Automatic power-off function
- Power by 4 AAA size alkaline batteries or AC/DC power supply

BLUETOOTH Blood Pressure Monitors

U80LH with BT

LCD size: 53x72mm
Product size: 132x100x45mm

- 2x90 memory
- WHO indicator
- Beep alarm
- Year/month/date/time function
- Power by 4 AA size alkaline batteries or AC/DC power supply
- 3 times average
- IHB indicator
- Automatic power-off



U80E with BT

LCD size: 55x44mm with digit height 18mm
Product size: 132x100x45mm

- 2x90 memory
- WHO indicator
- Beep alarm
- Year/month/date/time function
- Power by 4 AA size alkaline batteries or AC/DC power supply
- 3 times average
- IHB indicator
- Automatic power-off

U60EH with BT

LCD size: 46x35mm with digit height 13.3mm
Product size: 79x66x64.5mm

- 2x90 memory
- WHO indicator
- Automatic power-off
- Power by 2 AAA size alkaline batteries
- 3 times average
- IHB indicator
- Year/month/date/time function



APP is Ready for FREE

Support BLE smart phone

iOS - iPhone4S or later device

Android - All devices with BT4.0 and installed Android 4.3 or later (like Nexus 4, Nexus 5, Nexus 7, S4, Note 3, HTC One ...)

Digital blood pressure monitor with Bluetooth is a creative product that with a Bluetooth chip implanted in the ordinary digital blood pressure monitor, using Bluetooth wireless transmission function for the wireless transmission of measurement data.



iOS & Android



U80IH with BT

LCD size: 67.5x52mm with digit height 21mm
Product size: 139x95x45mm

- 2x90 memory
- 3 times average
- WHO indicator
- IHB indicator
- Year/month/date/time function
- Beep alarm
- Automatic power-off
- Power by 4 AA size alkaline batteries or AC/DC power supply

COLOR CHANGING Blood Pressure Monitors

U80FH

LCD size: 80x72mm
Product size: 139x100x46mm
• **Blue backlight for START /STOP button**



- 3 colors backlight for LCD
 - Optimal/Normal blood pressure
 - High normal value
 - Mid/Moderate/Severe hypertension

- 2x90 memory
- 3 times average
- WHO indicator
- IHB indicator
- Beep alarm
- Automatic power-off
- Year/month/date/time function
- Power by 4 AA size alkaline batteries or AC/DC power supply



U80JH

LCD size: 80x72mm
Product size: 139x100x46mm

U80K

LCD size: 80x72mm
Product size: 139x100x46mm
• **Blue backlight for LCD & START/STOP button**



U80J

LCD size: 80x72mm
Product size: 139x100x46mm
• **Blue backlight for LCD**

- 2x90 memory
- 3 times average
- WHO indicator
- IHB indicator
- Beep alarm
- Automatic power-off
- Year/month/date/time function
- Power by 4 AA size alkaline batteries or AC/DC power supply

U60GH

LCD size: 41.6x36.6mm
Product size: 69.5x66.5x60.5mm

- **LCD 1 color backlight (option)**
- **LCD 3 colors changing indicating (option)**
- **Bluetooth function (option)**



- 2x90 memory
- 3 times average
- WHO indicator
- IHB indicator
- Year/month/date/time function
- Automatic power-off
- Power by 2 AAA size alkaline batteries



U80K with Colorful Display

LCD size: 80x72mm
Product size: 139x100x46mm
• **Colorful display for digits**
• **Blue backlight for START/STOP button**



- 2x90 memory
- 3 times average
- WHO indicator
- IHB indicator
- Year/month/date/time function
- Beep alarm
- Automatic power-off
- Power by 4 AA size alkaline batteries or AC/DC power supply

DIGITAL Blood Pressure Monitors

U80L

LCD size: 67.5x52mm
Product size: 132x100x45mm

- 2x90 memory
- 3 times average
- WHO indicator
- IHB indicator
- Year/month/date/time function
- Beep alarm
- Automatic power-off
- Power by 4 AA size alkaline batteries or AC/DC power supply



U80EH Upgrade

LCD size: 76.8x60mm with digit height 22mm
Product size: 132x100x45mm

- Talking function
- Bluetooth function
- USB connect function, support to connect with Phone charger connector as for a power adapter (Output 6V-600mA)
- Power by 4 AA size alkaline batteries or AC/DC power supply or rechargeable Li-battery (can be used about 100 times when the charge is full)



U80E

LCD size: 55x44mm with digit height 18mm
Product size: 132x100x45mm

- 2x90 memory
- 3 times average
- WHO indicator
- IHB indicator
- Year/month/date/time function
- Beep alarm
- Automatic power-off
- Power by 4 AA size alkaline batteries or AC/DC power supply



- 2x90 memory
- 3 times average
- Year/month/date/time function
- WHO indicator
- IHB indicator
- Automatic power-off



U80C

LCD size: 55x44mm with digit height 18mm
Product size: 132x100x45mm

- 1x30 memory
- 3 times average
- IHB indicator
- Automatic power-off
- Power by 4 AA size alkaline batteries or AC/DC power supply



U80EH

LCD size: 76.8x60mm with digit height 22mm
Product size: 132x100x45mm

- 2x90 memory
- 3 times average
- WHO indicator
- IHB indicator
- Year/month/date/time function
- Beep alarm
- Automatic power-off
- Power by 4 AA size alkaline batteries or AC/DC power supply



DIGITAL Blood Pressure Monitors

U80AH

LCD size: 73x54mm
Product size: 140x113x65mm



U80IH

LCD size: 70x55mm with digit height 21mm
Product size: 139x95x42.5mm



U80N

LCD size: 73x54mm
Product size: 139x100x46mm



U80NH

LCD size: 80x72mm
Product size: 139x100x46mm
• Blue backlight for LCD



U80B

LCD size: 55x44mm with digit height 18mm
Product size: 130x109x60mm



U80BH

LCD size: 54x35mm
Product size: 130x109x60mm



U80KH

LCD size: 53x44mm
Product size: 132x100x45mm



U80LH

LCD size: 53x72mm
Product size: 132x100x45mm



- 2x90 memory
- 3 times average
- WHO indicator
- Automatic power-off
- Year/month/date/time function
- Beep alarm
- IHB indicator
- Power by 4 AA size alkaline batteries or AC/DC power supply

- 2x90 memory
- 3 times average
- WHO indicator
- Automatic power-off
- Year/month/date/time function
- Beep alarm
- IHB indicator
- Power by 4 AA size alkaline batteries or AC/DC power supply

DIGITAL WRIST Blood Pressure Monitors

U60AH

LCD size: 28.5x31.5mm with digit height 14mm
Product size: 66.5x63.5x55mm

- 2x90 memory
- 3 times average
- WHO indicator
- IHB indicator
- Year/month/date/time function
- Automatic power-off
- Power by 2 AAA size alkaline batteries



U60CH

LCD size: 47x39mm with digit height 14mm
Product size: 79x66x64.5mm

- 2x90 memory
- 3 times average
- WHO indicator
- IHB indicator
- Year/month/date/time function
- Automatic power-off
- Power by 2 AAA size alkaline batteries



U60BH

LCD size: 47x39mm with digit height 14mm
Product size: 79x66x64.5mm

- 2x90 memory
- 3 times average
- WHO indicator
- IHB indicator
- Year/month/date/time function
- Automatic power-off
- Power by 2 AAA size alkaline batteries



U60EH

LCD size: 46x35mm with digit height 14mm
Product size: 79x66x64.5mm

- 2x90 memory
- 3 times average
- WHO indicator
- IHB indicator
- Year/month/date/time function
- Automatic power-off
- Power by 2 AAA size alkaline batteries

NON-CONTACT Forehead Thermometers

UFR109

LCD size: 29x23mm

Product size: 158x47x29mm

• LCD with green backlight function

• LED indicator

- Measurement in progress
- Temperature < 37.5°C / 99.5°F
- Temperature ≥ 37.5°C

- Non-Contact measurement to forehead
- Measurement distance within 1.0cm
- 1s fast reading (Default)
- Beeper sound alarm
- Quick switch between body and object modes
- 20 sets of memories
- °C/°F Switchable
- Resolution: 0.1°C/°F
- Accuracy: ±0.2°C/±0.4°F (within 36.0°C~39.0°C/96.8°F~102.2°F);
- Low battery indication
- Measurement time interval in 15s
- Auto power-off / 60s
- Battery-powered / 2 x AAA (alkaline battery)
- Measuring range: body mode 32.0°C~ 43.0°C (89.6°F~109.4°F); object mode 0.0~100.0°C (32.0°F~199.9°F)



UFR106

LCD size: 32x28mm

Product size: 152x53x41mm

• LCD with blue backlight function

• With Bluetooth function (option)

• LED indicator

- Measurement in progress
- Temperature < 37.5°C / 99.5°F
- Temperature ≥ 37.5°C

- Non-Contact measurement to forehead
- Measurement distance within 1.0cm
- 1s fast reading (Default)
- Beeper sound alarm
- Quick switch between body and object modes
- 20 sets of memories
- °C/°F Switchable
- Resolution: 0.1°C/°F
- Accuracy: ±0.2°C/±0.4°F (within 36.0°C~39.0°C/96.8°F~102.2°F);
- Low battery indication
- Auto power-off / 60s
- Battery-powered / 2 x AAA (alkaline battery);
- Measuring range: body mode 32.0°C~ 43.0°C (89.6°F~109.4°F); object mode 0.0~100.0°C (32.0°F~199.9°F)



iOS & Android



Bluetooth



NON-CONTACT Forehead Thermometers

WFR110

Product size: 93x153x41mm

- Non-Contact measurement to forehead
- Measurement distance 5-15cm
- LCD 3 colors backlight indicating (white, orange, red)
- Quick switch between body and object modes
- 1s fast reading (Default)
- Beeper sound alarm
- 32 sets of memories
- Resolution: 0.1°C/°F
- Accuracy: $\pm 0.2^{\circ}\text{C}/\pm 0.4^{\circ}\text{F}$
- Auto power-off / 30s
- Battery-powered / 2 x AA (alkaline battery);
- Measuring range: body mode 32.0°C~42.9°C(89.6°F~109.2°F); object mode 0.0~100.0°C (32.0°F~199.9°F)



WFR107

Product size: 86x160x46mm

- Non-Contact measurement to forehead
- Measurement distance 5-15cm
- LCD Green color backlight indicating
- Quick switch between body and object modes
- 1s fast reading (Default)
- Beeper sound alarm
- 32 sets of memories
- Resolution: 0.1°C/°F
- Accuracy: body mode $\pm 0.2^{\circ}\text{C}/\pm 0.4^{\circ}\text{F}$; object mode $\pm 1.0^{\circ}\text{C}/\pm 1.8^{\circ}\text{F}$
- Auto power-off / 10s
- Battery-powered / 2 x AA (alkaline battery);
- Measuring range: body mode 32.0°C~42.9°C(89.6°F~109.2°F); object mode 0.0~100.0°C(32.0°F~199.9°F)



WFR108

LCD size: 26x21mm
Product size: 117x48x35mm

- Ear temperature, Forehead temperature, Object temperature, Clock and Environment temperature
- LCD with 3 colors backlight indicating: body mode
Green: 32.0°C~37.4°C
Orange: 37.5°C~37.9°C
Red: 38.0°C~42.9°C
- Last measurement memory function
- Resolution: 0.1°C/°F
- Accuracy: body mode $\pm 0.2^{\circ}\text{C}/\pm 0.4^{\circ}\text{F}$; object mode $\pm 1.0^{\circ}\text{C}/\pm 1.8^{\circ}\text{F}$
- Auto power-off
- Battery-powered: 1x 3V CR2032 button battery
- Measuring range: body mode 32.0°C~42.9°C(89.6°F~109.2°F); object mode 0.0~100.0°C(32.0°F~199.9°F)



WFR111

LCD size: 28x26mm
Product size: 152x44x30mm

- Ear temperature, Forehead temperature, Object temperature
- LCD with 2 colors backlight indicating (red and green), beeper alarm
- Measurement distance 5-15cm
- 20 sets of memories
- 1s fast reading (Default)
- °C/°F Switchable
- Accuracy: body mode $\pm 0.2^{\circ}\text{C}/\pm 0.4^{\circ}\text{F}$; object mode $\pm 1.0^{\circ}\text{C}/\pm 1.8^{\circ}\text{F}$
- Auto power-off/ 30s
- Battery-powered: 2 AAA alkaline battery
- Measuring range: body mode 32.0°C~42.9°C(89.6°F~109.2°F); object mode 0.0~100.0°C(32.0°F~199.9°F)



NON-CONTACT Forehead Thermometers

WFR112

LCD size: 30x45mm
Product size: 266x183x62mm



- Non-contact measurement to forehead
- LCD with 3 colors backlight indicating (white, orange and red), beeper alarm
- Year/Month/Date/Time and environment temperature display when idle
- Measurement distance 3-5cm
- 20 sets of memories
- 0.5s fast reading (Default)
- Accuracy: body mode $\pm 0.2^{\circ}\text{C}/\pm 0.4^{\circ}\text{F}$; object mode $\pm 1.0^{\circ}\text{C}/\pm 1.8^{\circ}\text{F}$
- Auto power-off/ 30s
- Battery-powered: 2 AAA alkaline battery
- Measuring range: body mode $32.0^{\circ}\text{C}\sim 42.9^{\circ}\text{C}(89.6^{\circ}\text{F}\sim 109.2^{\circ}\text{F})$; object mode $0.0\sim 100.0^{\circ}\text{C}(32.0^{\circ}\text{F}\sim 199.9^{\circ}\text{F})$

ET-100A

Product size: 134x70x34mm

- Measuring range: $34.0^{\circ}\text{C}\sim 44.0^{\circ}\text{C}$
- Accuracy: $\pm 0.2^{\circ}\text{C}$
- Min Scale: 0.1°C
- Auto power-off in 1min after non-use
- Power consumption: 0.6MW(working)
- Memory: 10 recordings
- Measuring time: 1 second
- Beeper alarm function
- Safe and Hygienic
- Battery: 1.5V AAA x2, Alkaline batteries
- Battery life: Approx 4000 times
- Require new disposable probe cover for each use



ET-100B

Product size: 114x35x40mm

- Measuring range: $34.0^{\circ}\text{C}\sim 44.0^{\circ}\text{C}$
- Accuracy: $\pm 0.2^{\circ}\text{C}$
- Min Scale: 0.1°C
- Auto power-off in 1min after non-use
- Power consumption: 0.6MW(working)
- Memory: 10 recordings
- Measuring time: 1 second
- Beeper alarm function
- Safe and Hygienic
- Battery: CR2032 3.0V 210MAH (lithium battery)
- Battery life: Approx 4000 times
- No probe filter, easy to clean



FT-100D

Product size: 158x45x35mm
LCD with 3 colors backlight display for different temperature range:
Green: $\leq 37.3^{\circ}\text{C}$
Orange: $37.4^{\circ}\text{C} \leq T < 38^{\circ}\text{C}$
Red: $\geq 38^{\circ}\text{C}$

- Multiple use: a. forehead temperature measuring; b. object temperature measuring; c. room temperature measuring
- Display Range & Accuracy:
 - a. Forehead temperature: $32^{\circ}\text{C}\sim 42.9^{\circ}\text{C}$, $\pm 0.3^{\circ}\text{C}$;
 - b. Surface of object temperature: $0^{\circ}\text{C}\sim 60^{\circ}\text{C}$, $\pm 1^{\circ}\text{C}$;
 - c. Room temperature: $0^{\circ}\text{C}\sim 40^{\circ}\text{C}$, $\pm 0.5^{\circ}\text{C}$
- Operation environment for forehead and surface of object: $10^{\circ}\text{C}\sim 40.0^{\circ}\text{C}$
- Measuring time: ≤ 1 second
- Min Scale: 0.1°C
- Reading store: 32 memories
- Battery: 3.0V (AAA x 2)
- Auto power-off in 1min after non-use
- $^{\circ}\text{C}/^{\circ}\text{F}$ switchable



FT-100A

Product size: 140x35x35mm
LCD with blue backlight

- Measuring range: $32.0^{\circ}\text{C}\sim 42.9^{\circ}\text{C}(89.6^{\circ}\text{F}\sim 109.2^{\circ}\text{F})$
- Accuracy: $\pm 0.3^{\circ}\text{C}(\pm 0.5^{\circ}\text{F})$
- Min Scale: 0.1°C
- Auto power-off in 1min after non-use
- Power consumption: 0.6MW(working)
- Memory: 10 recordings
- Measuring time: 1 second
- Beeper alarm function
- Safe and Hygienic
- Battery: 1.5V AAA x2, Alkaline batteries
- Battery life: Approx 4000 times
- Operating Temperature: $10.0^{\circ}\text{C}\sim 40.0^{\circ}\text{C}(50.0^{\circ}\text{F}\sim 104.0^{\circ}\text{F})$
- $^{\circ}\text{C}/^{\circ}\text{F}$ switchable



DIGITAL Thermometers

WDT101

Product size: 126x18x10mm



WDT102

Product size: 126x18x10mm
Soft head with metal tip



- Temperature range: 32.0°C~42.9°C
- Accuracy : ±0.1°C
- Display mode: LCD
- Power: 0.15mW(working)
- Beeper sound alarm
- Auto power-off function
- Measurement time: 30 seconds
- Battery: AG3 1.5V Ordinary button battery

DT-01B

Product size: 122x17x10mm



DT-11A

Product size: 133x18x13mm
• **Water-proof (perfect)**



- Measuring range: 32.0°C~42.0°C
- Accuracy: ±0.1°C(35.5°C~42.0°C)/ ±0.2°C(<35.5°C)
- Min. scale: 0.1°C
- Measurement time: 60 seconds
- Beeper sound alarm
- Memory: Last measuring reading
- Automatic power-off: within 10mins on after non-use
- Battery: One 1.5V(LR/SR41) button battery
- Battery life: About 100 hours under continuous operation

DT-101A

Product size: 126x18x10mm

- Measuring range: 32.0°C~42.0°C
- Accuracy: ±0.1°C(35.5°C~42.0°C)/ ±0.2°C(<35.5°C)
- Min. scale: 0.1°C
- Measurement time: 60 seconds
- Flexible tip
- Beeper sound alarm
- Memory: Last measuring reading
- Automatic power-off: within 10mins on after non-use
- Battery: One 1.5V(LR/SR41) button battery
- Battery life: About 100 hours under continuous operation



DT-111B

Product size: 125x20x11mm

- Waterproof (perfect quality)
- Flexible tip
- Measuring range: 32.0°C~42.0°C
- Accuracy: ±0.1°C(35.5°C~42.0°C)/ ±0.2°C(<35.5°C)
- Min. scale: 0.1°C
- Measurement time: 60 seconds
- Beeper sound alarm
- Automatic power-off: within 10mins on after non-use
- Battery: One 1.5V(LR/SR41) button battery
- Battery life: About 100 hours under continuous operation
- Fever alarm



DT-K01A

Product size: 134x22x14mm

- Measuring range: 32.0°C~42.0°C
- Accuracy: ±0.1°C(35.5°C~42.0°C)/ ±0.2°C(<35.5°C)
- Min. scale: 0.1°C
- Measurement time: 10 seconds
- Beeper sound alarm
- Memory: Last measuring reading
- Automatic power-off: within 10mins on after non-use
- Battery: One 1.5V(LR/SR41) button battery
- Fever alarm for temp greater than 37.8°C



Compressor Nebulizer

CN-C-0101

- Input: 220V /50Hz
- Power Consumption: 180VA
- Medication Capacity: 6cc
- Particle Size: respirable fraction 1 to 5µm 60%
- MMAD: 2.0µm
- Average Nebulization Rate: Above 0.15ml/min.
- Noise Level: Below 65 dBA
- Compressor Pressure Range: 30~45 Psi(2.1~3.2 bar)
- Operation Pressure Range: 10~16 Psi(0.69~1.1 bar)
- Liter Flow Range: above 5 lpm
- Operation Temperature Range: 10°C~40°C (50°F~104°F)
- Operation Humidity Range: 10~95% RH
- Storage Temperature Range:-20°C~70°C(-4°F~158°F)
- Storage Humidity Range: 10~95%RH
- Standard Accessories: nebulizer bottle, 1.6m air tube, mouth piece, adult mask, child mask, air filter (5pcs)



Product size: 195x174x98mm

WNE208

- Input: 220V /50Hz, 120V/60Hz
- Power Consumption: 175VA
- Medication Capacity: 8ml
- Particle Size: respirable fraction 0.5 to 5µm 75%
- MMAD: 2.0µm
- Average Nebulization Rate: Above 0.2ml/min.
- Noise Level: Below 60 dBA
- Compressor Pressure Range: 30~50 Psi(206 Kpa~345 Kpa)
- Operation Pressure Range: 9.5~20 Psi(65.5 Kpa~137.9 Kpa)
- Liter Flow Range: 6~10 lpm
- Operation Temperature Range: 10°C~40°C (50°F~104°F)
- Operation Humidity Range: 10~95% RH
- Storage Temperature Range:-20°C~70°C(-4°F~158°F)
- Storage Humidity Range: 10~95%RH
- Standard Accessories: Chamber, 1.6m air tube, mouth piece, adult mask, child mask, air filter (5pcs)



Product size: 168x180x103mm

WNE209

- Input: 220V /50Hz, 120V/60Hz
- Power Consumption: 175VA
- Medication Capacity: 8ml
- Particle Size: respirable fraction 0.5 to 5µm 75%
- MMAD: 2.0µm
- Average Nebulization Rate: Above 0.2ml/min.
- Noise Level: Below 60 dBA
- Compressor Pressure Range: 30~50 Psi(206 Kpa~345 Kpa)
- Operation Pressure Range: 9.5~20 Psi(65.5 Kpa~137.9 Kpa)
- Liter Flow Range: 6~10 lpm
- Operation Temperature Range: 10°C~40°C(50°F~104°F)
- Operation Humidity Range: 10~95% RH
- Storage Temperature Range:-20°C~70°C(-4°F~158°F)
- Storage Humidity Range: 10~95%RH
- Standard Accessories: Chamber, 1.6m air tube, mouth piece, adult mask, child mask, air filter (5pcs)



Product size: 190x185x171mm

Compressor Nebulizer

WNE203

Product size: 290x180x110mm

- Input: 230V /50Hz
- Power Consumption: 160VA
- Medication Capacity: 6cc
- Particle Size: respirable fraction 0.5 to 5µm 80%
- MMAD: 2.0µm
- Average Nebulization Rate: Above 0.2ml/min.
- Noise Level: Below 58 dBA
- Compressor Pressure Range: 30~45 Psi(2.1~3.2 bar)
- Operation Pressure Range: 10~16 Psi(0.69~1.1 bar)
- Liter Flow Range: 8~10 lpm
- Operation Temperature Range: 10°C~40°C (50°F~104°F)
- Operation Humidity Range: 10~95% RH
- Storage Temperature Range:-20°C~70°C(-4°F~158°F)
- Storage Humidity Range: 10~95%RH
- Standard Accessories: nebulizer bottle, air tube, mouth piece, adult mask, child mask, air filter (5pcs)



WNE206

Product size: 140x113x85mm

- Input: 220V /50Hz, 120V /60Hz
- Power Consumption: 175VA
- Medication Capacity: 6ml
- Particle Size: respirable fraction 0.5 to 5µm 80%
- MMAD: 2.0µm
- Average Nebulization Rate: Above 0.2ml/min.
- Noise Level: Below 63 dBA
- Compressor Pressure Range: 30~46 Psi(2.1~3.18 bar/210 Kpa~318 Kpa)
- Operation Pressure Range: 8~16 Psi(0.5~1.0 bar/50 Kpa~100 Kpa)
- Liter Flow Range: 6~10 lpm
- Operation Temperature Range: 10°C~40°C (50°F~104°F)
- Operation Humidity Range: 10~95% RH
- Storage Temperature Range:-20°C~70°C(-4°F~158°F)
- Storage Humidity Range: 10~95%RH
- Standard Accessories: nebulizer bottle, air tube, mouth piece, adult mask, child mask, air filter (5pcs)



WNE204

Product size: 290x170x100mm



WNE205

Product size: 160x140x95mm



WNE207

Product size: 190x135x135mm

